

# ENG SCIENTIFIC, LLC

121 Jersey Ave, 2<sup>nd</sup> Floor  
New Brunswick, NJ, USA 08901

## SAFETY DATA SHEET (SDS)

### #1 - IDENTIFICATION

**Product Identifier** – Trichrome Stain Kit (Solution VII)

**Product Code** – 6680, 6682, 6715, 6716

**Synonyms** – Carbol Xylene

**Recommended use** - Professional, scientific and medical-technical activities

**Recommended restrictions** - None known

**Manufacturer:**

**Company Name** - ENG Scientific, LLC  
121 Jersey Ave, 2<sup>nd</sup> Floor  
New Brunswick, NJ, USA 08901

**Contact Telephone** (973) 472 - 7200

**Toll Free** (800) 922 - 0223

**Website** [www.engscientific.com](http://www.engscientific.com)

**E-mail** [info@engscientific.com](mailto:info@engscientific.com)

**Emergency Contact** Chemtrec (800) 424-9300  
(217) 424-5200 ADM Corporate

### #2 - Hazard(s) Identification

**Physical hazards** Flammable liquid Category 3

**Health hazard** Highly flammable liquid and vapor Category 3

**Label elements**



**Signal word** Danger

**Hazard statement** Flammable liquid

**Precautions** Keep away from heat/open flames/hot surfaces

**Storage** Store at room temperature

**Supplemental info** Avoid release to the environment

**Disposal** Dispose of contents-according to local regulations

**NFPA Rating** - HEALTH: 3  
- FLAMMABILITY: 3  
- REACTIVITY: 0

### #3 – Composition

**Chemical name:** Xylene CAS # 1330-20-7  
Phenol CAS # 108-95-2

### #4 – First-aid measures

**Inhalation:** Remove to fresh air.

**Eye contact:** Remove contact lenses if worn. In case of contact, immediately flush eyes with plenty of clean running water for at least 15 minutes, lifting the upper and lower eyelids occasionally. Obtain medical attention.

**Skin contact:** Wash skin and clothing with soap and water.

**Swallowing:** If patient is fully conscious, give two glasses of water. Induce vomiting. This should be done only by Medical or experienced first aid personnel.

## **#5 – Fire-fighting measures**

**Extinguishing media:** Use water spray, carbon dioxide, dry chemical, alcohol-type, or universal type foams applied by manufacturer's recommended technique.

**Special fire-fighting procedures:** Ethanol burns with a clean clear flame that is almost invisible in daylight. Closed containers may rupture violently and suddenly release ethanol when exposed to fire or excessive heat for a sufficient period of time. Vapors are slightly heavier than air and may travel long distances toward sources of ignition.

## **#6 – Accidental release measures**

**Steps to be taken in case material is released or spilled:** Extinguish all sources of ignition; ventilate the area; flood or flush the area with water. Prevent spilled ethanol from entering sewers, confined spaces, drains, or waterways. Put material in suitable, covered, labeled containers. Flush area with water.

## **#7 – Handling and storage**

**Handling:** No smoking or open flame in storage, use or handling areas. Use explosion proof electrical equipment. Ensure proper grounding procedures are in place.

**Storage:** Store at room temperature and in a tightly closed container.

## **#8 – Exposure controls/personal protection**

**Respiratory protection:** NOISH - approved respirator.

**Ventilation:** General (mechanical) room ventilation recommended. Special local ventilation also recommended.

**Protective gloves:** Impermeable.

**Eye protection:** Chemical splash goggles or face shield.

**Other protective equipment:** Lab coat. Eye bath, safety shower.

## **#9 – Physical and chemical properties**

**Appearance:** Clear, colorless liquid.

**Odor:** Clear, bright sweet odor. **Boiling point:** 284<sup>o</sup>F

**Specific gravity:** (H<sub>2</sub>O = 1) 0.87 @ 20<sup>o</sup>C

**Vapor density:** (air = 1) >3.66 **Solubility in H<sub>2</sub>O** = Complete **Freezing point:** N/A **Evaporation Rate** = N/A

**Flash point:** 150<sup>o</sup>F, Tag Closed Cup ASTM D 56,

## **#10 – Stability and reactivity**

**Stability:** Stable as supplied.

**Incompatibility:** Reactive with acid and carbon oxides

**Conditions to avoid:** Avoid contact with sparks, heat, open flame, or ignition sources.

**Hazardous polymerization:** Will not occur.

## **#11 - Toxicology information**

### **Route of Exposure - Inhalation**

Prolonged inhalation of vapors causes dizziness, nausea, visual impairment, respiratory failure, muscular non-coordination and narcosis. Inhalation of high concentrations for prolonged periods has resulted in death. Liver damage has resulted from prolonged or repeated inhalation of vapors.

### **Route of Exposure - Skin**

Essentially non-irritating. Repeated or prolonged contact causes drying, brittleness, cracking and irritation. Slightly toxic to animals by absorption.

### **First Aid - Skin**

Remove contaminated clothing and wash contaminated skin with large amounts water. If irritation persists, contact a physician.

### **Route of Exposure - Eyes**

May cause eye injury which may persist for several days. Liquid and vapor in high concentrations, causes irritation, tearing and burning sensation.

### **First Aid - Eyes**

Flush eyes with water for at least 15 minutes. Contact a physician

### **Route of Exposure - Ingestion**

Poisonous if swallowed. Can affect the optic nerve resulting in blindness. Can cause mental sluggishness, nausea and vomiting leading to severe illness, possibly death (in humans). Practically non-toxic to animals.

### **Health Conditions Aggravated by Exposure**

Exposure may aggravate existing eye, skin, kidney and liver disorders. Pre placement and annual medical examinations are recommended for workers who normally handle methanol with emphasis on neurological, visual, liver and kidney functions. Monitoring of air in the work place is recommended to maintain methanol vapors below recommended TLV.

### **#12 – Ecological information**

**DO NOT** discharge into sewer or waterways. Small spills should be flushed with large quantities of water. Large spills should be collected for disposal. Flush with water, controlled burning.

### **#13 – Disposal considerations**

Disposal of hazardous material may be subject to federal, state or local regulations. The information contained in this document is believed to be factual, however, nothing presented herein is to be taken as a warranty or representation for which ENG Scientific, LLC shall be responsible.

### **#14 – Transport information**

**PROPER SHIPPING NAME:** Xylene

**UN NUMBER:** 1307

**HAZARD CLASS:** 3

**PACKING GROUP:** III

**DOT SHIPPING LABEL:** Flammable Liquid



*N/A For Limited Quantity*

### **#15 – Regulatory information**

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b)Export Notification (40 CFR 707, SUBPT. D)** Not regulated

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)** Not on regulatory list

**CERCLA Hazardous Substance List (40 CFR 302.4)** Xylene (CAS 1330-20-7) Phenol (CAS 108-95-2)

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Immediate Hazard – Yes

Delayed Hazard – Yes

Fire Hazard – Yes

Pressure Hazard – No

Reactivity Hazard – No

**SARA 302 Extremely hazardous substance** No

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:** Not regulated

**Clean Air Act (CAA) Section 112® Accidental Release Prevention (40 CFR 68.130):** Not regulated

**Clean Water Act (CWA) Section 112® (40 CFR 68.130):** Hazardous substance

**Safe Drinking Water Act (SDWA):** Not regulated

**Drug Enforcement Administration (DEA). List 2 Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and**

**Chemical Code Number:** Not listed

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c):**

Not regulated

**DEA Exempt Chemical Mixtures Code Number:** 594

**Food and Drug Administration (FDA):** N/A

**US state regulation:** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**US. Massachusetts RTK – Substance List:** Xylene (CAS 1330-20-7) Phenol (108-95-2)

**US. New Jersey Worker and Community Right-to-Know Act:** Xylene (CAS 1330-20-7) Phenol (CAS 108-95-2)

**US. Pennsylvania RTK – Hazardous Substances:** Xylene (CAS 1330-20-7) Phenol (CAS 108-95-2)

**US. Rhode Island RTK:** Xylene (1330-20-7) Phenol (CAS 108-95-2)

**US California Proposition 65:** WARNING

**US-California Proposition 65 – Carcinogens and Reproductive Toxicity (CRT):** Xylene (CAS 108-95-2)

**International Inventories**

<b>Country/Region</b>	<b>Inventory name</b>	<b>On Inventory*</b>
Canada	Non-domestic Substances List (NDSL)	No
Europe	European Inventory of Existing Chemical Substances (EINECS)	Yes
U.S.	Toxic Substances Control Act (TSCA) Inventory	Yes
Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*\* Yes complies with the inventory requirements administered by the governing country.*

**#16 – Other information**

**Issue date** January 31, 2022

**Version #** 05

**Further information** The information contained in this document is believed to be factual, however, nothing presented herein is to be taken as a warranty or representation for which ENG Scientific, LLC shall be responsible.